

# Data Sheet FUJITSU Storage ETERNUS DX60 S5 Disk System

The Economy Storage System for SMB



#### ETERNUS DX - Business-centric Storage

FUJITSU Storage ETERNUS DX series are the ideal hybrid storage for on-premise storage of businesscritical data in data centers, branch offices and self-operated IT of SMBs, something every business can afford, with integrated and powerful features for business growth, efficiency and continuity. Latest capacity and performance optimization capabilities contribute to overall business efficiency, outstanding connections and disk types enables choice in cost data-safe technologies and all-inclusive encryption guarantee uncompromised business continuity.

#### **ETERNUS DX60 S5**

Delivering reliable operation at an affordable price makes ETERNUS DX60 S5 an ideal disk storage system for small and medium-sized IT environments. Management software, included at no extra cost, reduces administration effort and provides the functionality to ensure data protection. Flexible support for different network and performance optimization. Designed for smaller environments, it provides remarkable scalability in storage capacity offering good headroom for future growth. Thus makes it the perfect storage solution for consolidation of distributed data and smaller server virtualization projects.



Page 1 / 6 www.fujitsu.com/eternus

### Features & Benefits

Benefits				
■ Best-in-class price/performance ratio				
■ Rich data safety functionality				
■ Enterprise feature set				
■ Single point administration				
■ Easy and efficient operation				
■ No extra cost for software package				
Ideal for small and medium-sized IT environments				
■ Easy to install, configure, operate and maintain				
Perfect fit for storage consolidation & virtualization				
<ul> <li>Serves the need of medium capacity requirements and predictable growth rates</li> </ul>				

Page 2 / 6 www.fujitsu.com/eternus

## Technical details

	2.5-inch Controller Enclosure	3.5-inch Controller Enclosure			
No. of controllers	1/2				
No. of host interfaces	4				
Maximum System Memory					
Maximum Disk Drives	96	48			
Max. no. of drive enclosures	3				
Supported RAID levels	0 1 1+0 5	0, 1, 1+0, 5, 5+0, 6			
Host Interfaces	Fibre Channel (16Gbit/s, 8Gbit/s)  iSCSI (10Gbit/s [10G BASE-T] / 1Gbit/s [1000 BASE-T])				
nost interfaces					
	SAS (120				
Max. no. of hosts	128				
Maximum Storage Capacity HDD	672 TB				
Maximum Storage Capacity SSD	31 TB				
Drive Type	2.5-inch, SAS, 15,000 rpm (9	900 GB / 600 GB / 300 GB)			
	2.5-inch, SAS, 10,000 rpm (2.4 TB/ 1	·			
	2.5-inch, SSD (3.84TE	·			
	3.5-inch, SAS, 10,000i				
	3.5-inch, Nearline SAS, 7,200 rpm (1 3.5-inch, SSI				
Max. no. of SSDs	3.5-III(II, 35L	(90006)			
Mixed 2.5 inch/ 3.5 inch drive enclosur					
Drive interface					
Back-end disk connectivity	Serial Attached SCSI (12 Gbit/s)  1 pair of four-lane x 12 Gbit/s Serial Attached SCSI buses (SAS 3.0 wide)				
Max. no. of RAID groups per system	1 pail of four faile x 12 abits serial 7				
Max. no. of LUNs per RAID group	128				
Max. no. of LUNs	1,024				
Max. LUN capacity					
Max. no. of copy generations	128 TB 512				
		-			
Performance	2 200 140 / /4	2010 0 1			
Sequential access performance	3,300 MB/s (1 940 MB/s (12	•			
Random access performance	65,000 IOPS (	·			
kandom access performance	29,000 IOPS (	•			
Information and the second	25,000 101 3 (	ond which			
Information security management	LITTOC (CCL) CCLL CLLA	D. Didisaskianal CHAD			
Data confidentiality	HTTPS (SSL), SSH, CHAP, Bidirectional CHAP  Data Block Guard, Cache Protection, Disk Drive Patrol, Global Hot Spare, Dedicated Hot Spare, Copy back less,				
Data integrity	Data Block Guard, Cache Protection, Disk Drive Patrol, Glob shield, Fast	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1			
Augilahiling ages sees t	Sinclu, Fasc				
Availability management	V				
Non-disruptive firmware upgrade	Yes				
Hot part replacement	Yes				
Capacity management					
Thin Provisioning	Yes				
RAID migration	Yes				
Reporting function	Yes				
Hot part expansion	Yes				
Management					
Administration	Web-based graphical user interface, CLI (Command Line Inte	rface), ETERNUS SF			

Page 3 / 6 www.fujitsu.com/eternus

Supported OS for ETERNUS SF						
Operation Management Server	Microsoft® Windows Servanicrosoft® Windows Servanicrosoft® Windows Servanicrosoft Windows Windows Windows Servanicrosoft Windows Windows Windows Windows Windows Windows Windows Window	ver® 2016 er 2012, 2012 R2 er) NUS SF Express) & 8 ux® 7 ux® 6 6.5, 6.7 er 2019 Hyper-V	er-V			
Operation Management Client	Internet Explorer® 9, 10 Firefox ESR 60, ESR 68 Microsoft Edge 25, 42, 4 Google Chrome 60, 75 Chrome® 47, 50 (Androi Safari 8, 9 (iOS)	, 11				
Note	See the ETERNUS SF data	See the ETERNUS SF datasheet for further options				
Supported configurations	Detailed support matrix:	All major host operating systems, servers and business applications Detailed support matrix: www.fujitsu.com/global/support/products/computing/storage/disk/supported-configrations				
Installation specification						
19" rackmount	Yes	Yes				
Power voltage	AC 100 - 120 V / AC 200	AC 100 - 120 V / AC 200 - 240 V				
Power frequency	50 / 60 Hz	50 / 60 Hz				
Maximum Power Consumption	AC 100 - 120 V: 1,990W (2030VA)					
Maximum Power Consumption	AC 200 - 240 V: 1,990W	AC 200 - 240 V: 1,990W (2030VA)				
Power phase	Single	Single				
	2.5-inch Controller Enclo	sure 3.5-inch Controller Enclo	sure 2.5-inch Drive Enclosure	3.5-inch Drive Enclosure		
Dimensions (W x D x H)	482 x 645 x 88 mm 19 x 25.4 x 3.5 inch 2 U	482 x 670 x 88 mm 19 x 26.4 x 3.5 inch 2 U	482 x 540 x 88 mm 19 x 21.3 x 3.5 inch 2 U	482 x 560 x 88 mm 19 x 22 x 3.5 inch 2 U		
Weight	35 kg (77 lb)	35 kg (77 lb)	35 kg (77 lb)	35 kg (77 lb)		
Environment						
Maximum Heat Generation	AC 100 - 120 V: 7,330: kJ/h AC 200 - 240 V: 7,330: kJ/h					
Humidity (operating)	20 - 80 %	20 - 80 %				
Operating environment		FTS 04230 – Guideline for Data Center (installation specification)				
Operating environment link	http://docs.ts.fujitsu.com	n/dl.aspx?id=589915e9-1bf8-4	40f7-8ba4-7cac9371f2f0			
Compliance						
Product safety	UL 60950-1, CSA 60950-	UL 60950-1, CSA 60950-1, EN 60950-1, IEC 60950-1, TP TC 004/2011, CNS14336				
Electromagnetic Compatibility	FCC Part-15 Class A, ICES-003 Class A, EN 55022 (2010), +AI, VCCI Class A, AS/NZS CISPR 22 Class A, CNS13438 (C6357) Class A, KN22					
Electromagnetic Immunity	EN 55024					
Environmental compliance	<u> </u>	RoHS compliant, WEEE compliant				
Compliance notes	There is general compliance with the safety requirements of all European countries and North America. National approvals required in order to satisfy statutory regulations or for other reasons can be applied for on request.					
Compliance link	https://sp.ts.fujitsu.com/	sites/certificates				
Warranty						
Warranty period	3 years					
Warranty type	Onsite warranty					

Page 4 / 6 www.fujitsu.com/eternus

Warranty	
Warranty Terms & Conditions Product Support Services - the perfe	www.fujitsu.com/warranty ect extension
Support Pack Options	Available in major business areas: 9x5, Next Business Day Onsite Response Time 9x5, 4h Onsite Response Time (depending on country) 24x7, 4h Onsite Response Time (depending on country)
Recommended Service	24x7, Onsite Response Time: 4h
Service Lifecycle	5 years after end of product life
Service Weblink	www.fujitsu.com/services/product-services

Page 5 / 6 www.fujitsu.com/eternus

#### Fujitsu products, solutions & services

In addition to FUJITSU ETERNUS DX60 S5, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

#### Fujitsu Portfolio

Built on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offerings. This allows customers to select from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

#### **Computing Products**

www.fujitsu.com/global/products/computing/

#### Software

www.fujitsu.com/software/

#### More information

Learn more about Fujitsu ETERNUS DX60 S5, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.

www.fujitsu.com/eternus

#### Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at http://www.fujitsu.com/qlobal/about/environment



#### Copyrights

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see http://www.fujitsu.com/emeia/resources/navigation/terms-of-use.html
Copyright 2019 FUJITSU LIMITED

#### Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.

#### Contact

FUJITSU LIMITED Website: www.fujitsu.com/eternus 2019-12-03 WW-EN

Page 6 / 6 www.fujitsu.com/eternus