



# HPE Altoline 6921 Switch Series

## Key features

- High-density 10GbE ports and low latency for demanding applications
- Open networking and disaggregated solution for customer choice
- ONIE boot loader for choice of network OS and easy installation
- VXLAN L2 and L3 for efficient network virtualization overlay solutions
- Intel® quad-core x86 Atom CPU and Broadcom Trident II+ controller,
- Redundant fans, and power supplies for data center deployments

## Product overview

HPE Altoline 6921 Switch Series are top-of-rack (ToR) leaf switches for high-performance cloud data centers in a compact 1RU form factor. The switches provide line-rate L2 and L3 switching across up to 48 1/10GBASE-T or 1/10GbE SFP+ ports, with 6 x 40GbE QSFP+ uplinks.

HPE Altoline 6921 Switch Series is designed to be deployed as leaf ToR switches supporting 1/10GbE server connections.

In HPE Altoline 6921 Switch Series, bare-metal switches are loaded with the Open Network Install Environment (ONIE), which supports installing and uninstalling of compatible third-party switch Network Operating System (NOS) offerings.

## Features and benefits

### Data center optimized

- Flexible high-port density  
HPE Altoline 6921 Switch Series enables scaling of the server edge with 1/10GbE copper or fiber server connections, with 40GbE uplinks, to new heights with high density in 1RU design.
- High-performance switching  
Cut-through and non-blocking Trident II+ ASIC delivers low latency (720 nanosecond) for very demanding cloud data center applications; the switch delivers high-performance switching capacity and wire-speed packet forwarding

- Hot or cold aisle support  
Models available with front-to-back (port-to-power) or back-to-front (power-to-port) airflow
- Redundant fans and power supplies  
1+1 internal redundant and hot-pluggable power supplies and N+1 redundant fan trays enhance reliability and availability
- VXLAN hardware support  
Supports VXLAN L2 and L3 VTEP overlay technologies; can terminate and forward VXLAN tunnels; supports over 16 million VXLAN IDs

#### **Manageability**

- Out-of-band interface  
Isolates management traffic from user-data plane traffic for complete isolation and total reachability, no matter what happens in the data plane
- ONIE boot loader  
Switch is loaded with the ONIE boot loader for NOS installation and uninstallation
- Intel x86 CPU (quad-core Atom)  
Provides high-performance support of widely available, industry-standard software and utilities

#### **L2 switching**

- VLAN support  
Provides support for 4,096 VLAN IDs

#### **Additional information**

- Low-power consumption  
SFP version maximum power: 282 W, without pluggable optics and Base-T version maximum power: 348 W

#### **Warranty and support**

- 1-year warranty  
See [hpe.com/networking/warrantysummary](http://hpe.com/networking/warrantysummary) for warranty and support information included with your product purchase.
- Software releases  
To find software for your product, refer to [hpe.com/networking/support](http://hpe.com/networking/support); for details on the software releases available with your product purchase, refer to [hpe.com/networking/warrantysummary](http://hpe.com/networking/warrantysummary)

## HPE Altoline 6921 Switch Series

### Specifications

	HPE Altoline 6921 48SFP+ 6QSFP+ x86 ONIE AC Front-to-Back Switch (JL317A)	HPE Altoline 6921 48SFP+ 6QSFP+ x86 ONIE AC Back-to-Front Switch (JL318A)
<b>I/O ports and slots</b>	48 SFP+ 1/10GbE ports (IEEE 802.3ae Type 10GBASE-ER, IEEE 802.3ae Type 10GBASE-LR, IEEE 802.3ae Type 10GBASE-SR, IEEE 802.3z Type 1000BASE-SX, IEEE 802.3z Type 1000BASE-LX)  6 QSFP+ 40GbE ports	48 SFP+ 1/10GbE ports (IEEE 802.3ae Type 10GBASE-ER, IEEE 802.3ae Type 10GBASE-LR, IEEE 802.3ae Type 10GBASE-SR, IEEE 802.3z Type 1000BASE-SX, IEEE 802.3z Type 1000BASE-LX)  6 QSFP+ 40GbE ports
<b>Additional ports and slots</b>	1 RJ-45 serial console port 1 RJ-45 out-of-band management port 1 USB 2.0	1 RJ-45 serial console port 1 RJ-45 out-of-band management port 1 USB 2.0
<b>Power supplies</b>	2 power supply slots 1 minimum power supply required includes: 2 x PSUs	2 power supply slots 1 minimum power supply required includes: 2 x PSUs
<b>Fan tray</b>	5 fan tray slots Switch comes with five (5) fan trays (front-to-back airflow)	5 fan tray slots Switch comes with five (5) fan trays (back-to-front airflow)
<b>Physical characteristics</b>		
Dimensions	17.4(w) x 18.6(d) x 1.71(h) in. (44.2 x 47.24 x 4.34 cm)	17.4(w) x 18.6(d) x 1.71(h) in. (44.2 x 47.24 x 4.34 cm)
Weight	18.74 lb (8.5 kg)	18.74 lb (8.5 kg)
<b>Memory and processor</b>	Intel Atom C2538 quad-core x86 processor @ 2.4 GHz, 8 GB DDR3 SDRAM; Packet buffer size: 12 MB, 8 GB NAND flash ASIC: Trident II+	Intel Atom C2538 quad-core x86 processor @ 2.4 GHz, 8 GB DDR3 SDRAM; Packet buffer size: 12 MB, 8 GB NAND flash ASIC: Trident II+
<b>Performance</b>		
Latency	720 ns	720 ns
Throughput	Up to 1 Bpps	Up to 1 Bpps
Routing/Switching capacity	1440 Gbps	1440 Gbps
Routing table size	64000 entries (IPv4), 20000 entries (IPv6)	64000 entries (IPv4), 20000 entries (IPv6)
MAC address table size	320000 entries	320000 entries
<b>Environment</b>		
Operating temperature	32°F to 104°F (0°C to 40°C)	32°F to 104°F (0°C to 40°C)
Operating relative humidity	5% to 95%, noncondensing	5% to 95%, noncondensing
Non-operating/Storage temperature	-40°F to 158°F (-40°C to 70°C)	-40°F to 158°F (-40°C to 70°C)
Airflow direction	Front-to-back	Back-to-front

## HPE Altoline 6921 Switch Series

### Specifications (continued)

	HPE Altoline 6921 48SFP+ 6QSFP+ x86 ONIE AC Front-to-Back Switch (JL317A)	HPE Altoline 6921 48SFP+ 6QSFP+ x86 ONIE AC Back-to-Front Switch (JL318A)
<b>Electrical characteristics</b>		
Frequency	50/60 Hz	50/60 Hz
Voltage	90 - 264 VAC, rated	90 - 264 VAC, rated
Maximum power rating	282 W	282 W
Idle power	267 W	267 W
Notes	Idle power is the actual power consumption of the device with no ports connected. Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated. PSU Efficiency: Up to 93% for AC PSUs	Idle power is the actual power consumption of the device with no ports connected. Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated. PSU Efficiency: Up to 93% for AC PSUs
<b>Safety</b>	cUL Certified; EN 60950; EN 55022 Class A; VCCI Class A; RoHS Compliance; FCC Class A; Regulations for Radio Frequency Devices for Electromagnetic Compliance; UL	cUL Certified; EN 60950; EN 55022 Class A; VCCI Class A; RoHS Compliance; FCC Class A; Regulations for Radio Frequency Devices for Electromagnetic Compliance; UL
<b>Emissions</b>	FCC part 15 Class A; EN 55022 Class A; VCCI; EN 60950-1	FCC part 15 Class A; EN 55022 Class A; VCCI; EN 60950-1
<b>Immunity</b>		
ESD	EN 60950	EN 60950
EFT/Burst	IEC 68-2-14	IEC 68-2-14
<b>Management</b>	Command-line interface; out-of-band management; SNMP manager; Telnet; FTP	Command-line interface; out-of-band management; SNMP manager; Telnet; FTP
<b>Services</b>	Refer to the Hewlett Packard Enterprise website at <a href="http://hpe.com/networking/services">hpe.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.	Refer to the Hewlett Packard Enterprise website at <a href="http://hpe.com/networking/services">hpe.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.

## HPE Altoline 6921 Switch Series

### Specifications (continued)

	HPE Altoline 6921 48XGT 6QSFP+ x86 ONIE AC Front-to-Back Switch (JL315A)	HPE Altoline 6921 48XGT 6QSFP+ x86 ONIE AC Back-to-Front Switch (JL316A)
<b>I/O ports and slots</b>	48 1/10GBASE-T ports 6 QSFP+ 40GbE ports	48 1/10GBASE-T ports 6 QSFP+ 40GbE ports
<b>Additional ports and slots</b>	1 RJ-45 serial console port 1 RJ-45 out-of-band management port 1 USB 2.0	1 RJ-45 serial console port 1 RJ-45 out-of-band management port 1 USB 2.0
<b>Power supplies</b>	2 power supply slots 1 minimum power supply required includes: 2 x PSUs (C)	2 power supply slots 1 minimum power supply required includes: 2 x PSUs (C)
<b>Fan tray</b>	5 fan tray slots Switch comes with five (5) fan trays (front-to-back airflow)	5 fan tray slots Switch comes with five (5) fan trays (back-to-front airflow)
<b>Physical characteristics</b>		
Dimensions	17.4(w) x 18.6(d) x 1.71(h) in. (44.2 x 47.24 x 4.34 cm)	17.4(w) x 18.6(d) x 1.71(h) in. (44.2 x 47.24 x 4.34 cm)
Weight	18.74 lb (8.5 kg)	18.74 lb (8.5 kg)
<b>Memory and processor</b>	Intel Atom C2538 quad-core x86 processor @ 2.4 GHz, 8 GB DDR3 SDRAM; Packet buffer size: 12 MB, 8 GB NAND flash ASIC: Broadcom Trident II+	Intel Atom C2538 quad-core x86 processor @ 2.4 GHz, 8 GB DDR3 SDRAM; Packet buffer size: 12 MB, 8 GB NAND flash ASIC: Broadcom Trident II+
<b>Performance</b>		
Latency	720 ns	720 ns
Throughput	Up to 1 Bpps	Up to 1 Bpps
Routing/Switching capacity	1440 Gbps	1440 Gbps
Routing table size	64000 entries (IPv4), 20000 entries (IPv6)	64000 entries (IPv4), 20000 entries (IPv6)
MAC address table size	320000 entries	320000 entries
<b>Environment</b>		
Operating temperature	32°F to 104°F (0°C to 40°C)	32°F to 104°F (0°C to 40°C)
Operating relative humidity	5% to 95%, noncondensing	5% to 95%, noncondensing
Non-operating/Storage temperature	-40°F to 158°F (-40°C to 70°C)	-40°F to 158°F (-40°C to 70°C)
Airflow direction	Front-to-back	Back-to-front

## HPE Altoline 6921 Switch Series

### Specifications (continued)

	HPE Altoline 6921 48XGT 6QSFP+ x86 ONIE AC Front-to-Back Switch (JL315A)	HPE Altoline 6921 48XGT 6QSFP+ x86 ONIE AC Back-to-Front Switch (JL316A)
<b>Electrical characteristics</b>		
Frequency	50/60 Hz	50/60 Hz
Voltage	90–264 VAC, rated	90–264 VAC, rated
Maximum power rating	282 W	282 W
Idle power	267 W	267 W
Notes	Idle power is the actual power consumption of the device with no ports connected. Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated. PSU Efficiency: Up to 93% for AC PSUs	Idle power is the actual power consumption of the device with no ports connected. Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated. PSU Efficiency: Up to 93% for AC PSUs
<b>Safety</b>	cUL Certified; EN 60950; EN 55022 Class A; VCCI Class A; RoHS Compliance; FCC Class A; Regulations for Radio Frequency Devices for Electromagnetic Compliance; UL	cUL Certified; EN 60950; EN 55022 Class A; VCCI Class A; RoHS Compliance; FCC Class A; Regulations for Radio Frequency Devices for Electromagnetic Compliance; UL
<b>Emissions</b>	FCC part 15 Class A; EN 55022 Class A; VCCI; EN 60950-1	FCC part 15 Class A; EN 55022 Class A; VCCI; EN 60950-1
<b>Immunity</b>		
ESD	EN 60950	EN 60950
EFT/Burst	IEC 68-2-14	IEC 68-2-14
<b>Management</b>	Command-line interface; out-of-band management; SNMP manager; Telnet; FTP	Command-line interface; out-of-band management; SNMP manager; Telnet; FTP
<b>Services</b>	Refer to the Hewlett Packard Enterprise website at <a href="http://hpe.com/networking/services">hpe.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.	Refer to the Hewlett Packard Enterprise website at <a href="http://hpe.com/networking/services">hpe.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.

Learn more at  
[hpe.com/networking](http://hpe.com/networking)





---

**Sign up for updates**

---



---

© Copyright 2016 Hewlett Packard Enterprise Development LP. The information contained herein is subject to change without notice. The only warranties for Hewlett Packard Enterprise products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. Hewlett Packard Enterprise shall not be liable for technical or editorial errors or omissions contained herein.

Intel is a trademark of Intel Corporation in the U.S. and other countries. All other third-party trademark(s) is/are property of their respective owner(s).

4AA6-7103ENW, September 2016