

Ibm UPS 10000XHV (21304RX)

UPS 10000XHV



Now you can protect and substantially extend the backup power runtimes of your mission-critical applications with cost-effective, high-availability, uninterruptable power supply (UPS) options.

Main specifications:

Energy management

Output power capacity (VA): 10000 VA
Power supply input frequency: 50 - 60 Hz

Connectivity

USB 2.0 ports quantity: 1
Serial ports quantity: 1
Ethernet LAN (RJ-45) ports quantity: 1

Technical details

Form factor: Rack 6U

Battery

Battery technology: Sealed Lead Acid
Typical backup time at half load: 13 min

Weight & dimensions

Weight: 109000 g

Networking

Networking features: Ethernet, Fast Ethernet

Other features

Output connections: 4 x IEC 320 (EN 60320) C20
Dimensions (WxDxH): 430 x 685 x 267 mm
Nominal input voltage: 200 - 240 / 380 - 415 V
Compatible operating systems: Microsoft Windows NT Server 4.0, Microsoft Windows 2000 Server, Microsoft Windows 2000 Advanced Server, Microsoft Windows XP Professional, Microsoft Windows Server 2003 Enterprise Edition, Microsoft Windows Server 2003 Web Edition, Microsoft Windows Server 2003 Standard Edition, Novell NetWare 6.5, Red Hat Enterprise Linux AS 3 - Intel x86, Red Hat Enterprise Linux WS 3 - Intel x86, Red Hat Enterprise Linux ES 3 - Intel x86

*PLEASE NOTE: Every effort has been made to ensure the accuracy of all information contained herein. Lasystems makes no warranty expressed or implied with respect to accuracy of the information, including price, editorials or specifications. Lasystems or its suppliers shall not be liable for incidental, consequential or special damages arising from, or as a result of, any electronic transmission or the accuracy of the information contained herein, even if Lasystems has been advised of the possibility of such damages. Product and manufacturer names are used only for the purpose of identification.